



Professional Hair Labs™
World Leader in Cosmetic Bonding



Phone:

USA: 1.800.778.4247
UK: +44 (0)20 3286 0094
Germany: +49 (0)30 2089 6831
Ireland: +353.(0)1.442.8808

Media:

Web: <http://www.prohairlabs.com>
Email: info@prohairlabs.com
Facebook: Professional Hair Labs

Address:

USA: 4775 Allen Road, Zephyrhills, Florida 33541
Ireland: Avalon, Sinnottstown Lane, Drinagh, Wexford

Material Safety Data Sheet

Commercial product name: **No Sweat**
Date of print: 25.05.2011

1. Identification of the substance/preparation and of the company/undertaking

1.0 Identification of the substance or preparation:
Commercial Product Name: No Sweat
Version: 1

1.1 Company/undertaking identification:

| | | |
|--------------------------|---|--|
| Manufacturer/Distributor | : | PHL Inc |
| Street: | | 4775 Allen Road |
| City: | | Zephyrhills |
| State: | | Florida |
| Zip: | | 33541 |
| Country: | | USA |
| Telephone: | | +1.813.788.7468 |
| Fax: | | +1.813.788.7983 |
| Emergency: | | +1.813.788.7468 |
| E-Mail: | | info@prohairlabs.com |

Component Information

Specify Chemical Identity; Common Name(s):

Aluminum Chlorohydrate - CAS#S 1327-41-9/OSHA PEL/ACGIH TLV/OTHER LIMITS
Optional <10%

Physical/Chemical Characteristics

- Boiling Point: 200 F
- Vapor Pressure: N/A
- Vapor Density: N/A
- Presence: Clear Liquid With Floral Scent
- Specific Gravity (Water-1): 0.889
- Melting Point: 20 F
- Evaporation Rate: 1.22

Fire and Explosion Hazard Data

- Flash Point: 80 F
- Extinguishing Media: Dry Powder#
- Special Fire Fighting Procedures: NONE

Reactivity Data

- Incompatibility (Materials to Avoid): NONE
- Hazardous Polymerization: WILL NOT OCCUR

Health Hazard Data

- Routes of Entry : Inhalation - X / Skin - O / Ingestion - X
- Health Hazards : Acute and Chronic
- Signs and Symptoms of Exposure: Headache/Upset Stomach
- Medical Conditions Generally Aggravated By Exposure: None Known

Emergency and First Aid Procedures

In case of eye contact flush eyes with running water for 15 minutes. If irritation persists please obtain medical aid. For skin contact, wash with soap and water and remove contaminated clothes. If swallowed, do not induce vomiting. Drink two glasses of water and call a physician immediately for discomfort of inhalation. Bring person outside to fresh air.

Steps To Be Taken If Material Is Released Or Spilled

- Absorb with inert material after diluting with water.
- Store in a cool dry place with adequate ventilation.
- Approved landfill in accordance with local state and federal regulations.

Control Measures

| | |
|----------------------------|-----------------------------|
| Protective Gloves: | Rubber |
| Eye Protection: | Safety Glasses |
| Working Hygiene Practices: | Use good working practices. |

We believe that the information contained here is current as the date on the material safety data sheet. OSHA section 1810 1200 has been applied. This states that if one of more hazardous components are a level of 1% or greater, then the mixture is presumed to have all of the health hazards of the components. Since the use of products is not within our control, it is the users obligation to determine the conditions of safe use of this product.

Other information

n.a. = not applicable n.s. = not subject to

No Sweat has been developed for use as a anti perspirant for the skin. If No Sweat is to be used for another process, the user should verify, by means of tests etc, that the product is suitable for the intended application.

The above information describes exclusively the safety requirements for the product(s) and is based on our present-day knowledge. It does not represent a guarantee for the properties of the product(s) described in terms of the legal warranty regulations. The delivery specification is to be found in the respective product leaflet.

The information contained in this sheet does not constitute a hazard assessment, and should not be used in place of the user's own assessment of workplace risks as required by other health and safety legislation. Our data and suggestions are based on information which we believe to be reliable. Users should verify by tests that our product as well as suggested methods are suitable with the product / materials being used in their application. Since specific use, materials and handling are not controlled by us, our warranty is limited to the replacement of any defective product supplied by us. Full technical support is available from our trained sales staff.